

# Smart Klass 786



"SMART KLASS – Std 16"	
Caliber	7.62 x 51mm
Operating Principle	Direct Gas Impingement
Locking System	Locked Breech Rotating Bolt
Barrel Length	STD: 16 in CQC: 14 in, DMR: 20 in
Rifling Principle	254mm – 10 in
Number of Grooves	R.H – 6 Grooves
Weight (Empty Magazine)	< 4.0 KG
Sights System	Flip – up Iron / Diopter
Magazine Capacity	20 Rounds
Stock	4 Positions
Length Min / Max	Approx. 865-950mm
Safeties	Manual Safety
Fire Selector Positions	Safe – Semi - Auto
Ejection Side	Right
Thermoset Hand Guard	Fiberglass Reinforced Techno Polymer
Accessory Rail	MIL – STD - 1913
Accessories (Optional)	Thermal Sights, Scope

## FEATURES

High Reliability

Accurate  
(< 3 MOA for STD Rnds)

Operational Suitability for  
extreme weathers (-40° C to +60° C)

Monolithic Extruded Upper Receiver

Fully Ambidextrous Design

Non-Reciprocating Charging Handle

Heat-Resistant Techno Polymer  
Hand Guard

Conformance to MIL –  
SPECS Standards

Ease of Operation /  
Field Maintenance



  
**DynTek**  
Engineering

Marketing Partner



Block 11, Alpha Techno Square, Old International Airport, Rawalpindi - Pakistan

☎ 051-5404004 ☎ 051-5405003

✉ info@dyntekengg.com 🌐 www.dyntekengg.com